



# EQAS CH Baptistry Heater

The most cost effective heater in the industry !



17" H, 5.2"W, 6" D  
24 lbs

## FEATURES:

120 volt / 240 volt field selectable

5500 watts of heating @ 240 volt  
4600 watts of heating @ 208 volt  
1300 watts of heating @ 120 volt

Full Range Thermostat

Set it to your comfort level and forget it

High Limit Protected

Keeps water at a safe temperature

Pressure Switch Activated

Heater won't activate without water in the heater tube

UL Listed  
(UL1563)

## What's in the box ?

1. Heater
2. Pump—plugs into heater for power.  
No separate circuit required
3. Air button with 20' tubing for start/ stop control
4. 2 Suction fittings for baptistry wall
5. 1 return fitting for baptistry wall
6. All necessary pump & heater fittings
7. Instruction Sheet

### You will need:

1. GFCI protected circuit (generally installed in the breaker box) run to the heater
2. 1 1/2" PVC pipe, fittings, & glue for suction and return line
3. Polyurethane Sealant for baptistry wall fittings

## GFCI REQUIRED (Ground Fault Circuit Interrupter)

240V Requires GFCI 2P30A breaker  
or in-line device

208V Requires GFCI 2P30A breaker  
or in-line device

120v Requires GFCI 1p15A breaker  
or in-line device

**Failure to install this safety device may result in death**